

DEWALT®

ENLARGED BATTERY BOX

To allow use of the DCB615
(This Battery Sold Separately)



DCS692

FLEXVOLT® 60V MAX* CORDLESS BRUSHLESS 9 IN. CUT-OFF SAW



DCS692



CUTS THROUGH
#5 (5/8 IN.) REBAR**



CHANNELING CUTS IN
STANDARD SIZE (16 IN. X
8 IN. X 8 IN.) CINDERBLOCK†



CINDERBLOCKS
CUT IN HALF††

USING DCB609 BATTERY
(INCLUDED WITH DCS692X2)

96

44

22

USING DCB615 BATTERY
(SOLD SEPARATELY)

191

103

51

STOPS
38% FASTER
THAN THE MILWAUKEE 2786-20§



* Maximum initial battery voltage (measured without a workload) is 60 volts. Nominal voltage is 54.

** Per charge, cutting 4-piece rebar bundles using DWAFV8918 Abrasive Wheel.

† Per charge, using DWAFV8900 Diamond†† Cutting Blade in standard cored block. Standard cored concrete block is 16 in. x 8 in. x 8 in. with a thickness of 1 in., Depth of cut is 3-1/4 in.

†† Per charge, cutting 16 in. x 8 in. x 8 in. standard cored concrete block using DWAFV8900 Diamond†† Cutting Blade. Concrete block has a thickness of 1 in.

§ On average, using DWAFV8900 Diamond†† Cutting Blade (sold separately) vs. 2786-20 used with 48-11-1812 battery and 49-93-7025 blade. Milwaukee is a registered trademark of Milwaukee Electric Tool Corporation which has not endorsed or approved this comparison.

†† Blade uses manufactured diamonds engineered for cutting.

GUARANTEED TOUGH.®

DCS692SS

FLEXVOLT® 60V MAX* CORDLESS BRUSHLESS 9 IN. CUT-OFF SAW



DUAL-SIDED WATER DELIVERY SYSTEM

For dust management when cutting concrete

ROTATABLE GUARD

5-position for optimized approach angle and visibility when cutting in tight spots

HEAVY LOAD INDICATOR

Provides user feedback during demanding applications without stopping them short of completion

ENLARGED BATTERY BOX

To allow use of the DCB615 (This Battery Sold Separately)



OPTIMIZED DEPTH OF CUT

3-1/4 in. depth of cut for single pass in pavestones, rebar cutting and concrete scoring

ALL-METAL DRIVETRAIN

For durability and efficiency

LATCHED BATTERY BOX

Helps keep water and airborne dust out

2-STAGE TRIGGER

Helps prevent accidental activation



Tool Tag not included.



DESIGNED TO ENHANCE PRODUCTIVITY

For use with future DeWALT products. Connect to other compatible DeWALT tools and operate cord-free on the jobsite with WIRELESS TOOL CONTROL™

TOOL WARRANTY

**3
YEAR**

LIMITED
WARRANTY

**1
YEAR**

FREE
SERVICE

**90
DAY**

MONEY BACK
GUARANTEE



Makes fast and efficient single pass cuts and scores in concrete, pavestones, steel, and rebar.

SPECIFICATIONS

NO LOAD SPEED	6,600 rpm
BLADE DIAMETER	9 in.
ARBOR SIZE	7/8 in.
DEPTH OF CUT	3-1/4 in.
ROTATABLE GUARD	5-Position
WATER CONNECTION	Yes (with Valve)
TOOL WEIGHT	11.29 lbs. (Tool Only)

MODELS AVAILABLE

DCS692X2

- (2) DCB609 Batteries
- (1) DWAFV8918 Ceramic Metal Cut-Off Wheel
- (1) DWAFV8900 Diamond^{††} Cutting Blade
- (1) DCB118 Fast Charger

DCS692B

- (1) DWAFV8918 Ceramic Metal Cut-Off Wheel
- (1) DWAFV8900 Diamond^{††} Cutting Blade

^{††}This blade uses manufactured diamonds engineered for cutting.

RELATED ACCESSORIES

DWAFV8918

DEWALT FLEXVOLT® 9 in. Ceramic Metal Cut-Off Wheel Type 1

High grain concentration for smooth, aggressive cutting



DWAFV8900

DEWALT FLEXVOLT® 9 in. Diamond^{††} Cutting Blade

Segmented diamond cutting edge for long life in concrete cutting and scoring

^{††}This blade uses manufactured diamonds engineered for cutting.



Copyright © 2023 DeWALT. The following are examples of trademarks for one or more DeWALT power tools and accessories: the yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

DCS692SS

GUARANTEED TOUGH.

1-800-4-DEWALT

www.DEWALT.com